

KOHLER Generators

Full Line Preview

Trusted by the National Weather Service

To keep their remote stations operating during power outages, the National Weather Service and National Oceanic and Atmospheric Administration depend on KOHLER® home generators.



Get more great information.
Then find your local dealer at KohlerGenerators.com.

KOHLER Generators

KOHLER GENERATORS ■ KOHLER, WISCONSIN 53044

Printed in U.S.A. 09/12 G12-392 © 2012 Kohler Co.
KOHLER®, OnCue®, and Command PRO® are trademarks of Kohler Co.
Use of this material for reproduction on the Internet and World Wide Web is strictly prohibited without written permission from Kohler Co.



THE ANSWER TO MOTHER NATURE'S MOOD SWINGS.

Keep the lights on, the movie playing and the coffee brewing. Whatever the weather's doing doesn't matter. Because unlike portable generators, KOHLER® generators restore your power automatically and keep you connected to what you love to do.

You can trust a KOHLER generator – for good reasons.

It just works.

Every KOHLER generator is extensively quality-tested – before model release *and* before leaving the factory. The result is total reliability.

It can power everything.

In as little as 10 seconds, it automatically powers your AC, heat, sump pump and major appliances like your fridge and oven. All at the same time.*

It comes with the best warranty.

You get our exclusive 5-year, 2,000-hour protection, plus a corrosion-proof enclosure that's built to last.**

It protects your electronics.

A KOHLER generator creates steady, high-quality power, which means your electronics are protected from erratic power surges.

It's trusted everywhere.

Hospitals, nuclear power plants and even the National Weather Service trust in hard-working, long-lasting KOHLER generators.

*Based on generator and load size.

**14 and 20 kW models feature corrosion-proof enclosures; all other models feature corrosion-resistant enclosures.

Find the perfect size for your needs.



Model number	8.5RES	14RESA	20RESA	30RESA	38RCL	48RCL	60ERESB	80ERESD	100ERESD	125ERESB
Rated Power LPG/NG (kW)	8.5/7.0	14/12	20/18	30/27	38/38	48/48	60/60	NA/80	80/100	112/125
Voltage @ 60 Hz	120/240	120/240	120/240	120/240	120/240	120/240	120/240	120/240	120/240	120/240
Amps LPG/NG @ 240 V	35/29	58/50	83.3/75	125/112	158/158	200/200	250/250	NA/333	333/417	467/521
Engine/Alternator RPM	3600	3600	3600	3600	1800	1800	1800	1800	1800	1800
Engine	624 cc	725 cc	999 cc	1.6 L	4.3 L	5.0 L	5.7 L	5.7 L Turbo	5.7 L Turbo	8.1 L Turbo
	15.4 hp	23.6 hp	30.9 hp	52 hp	75 hp	89 hp	105 hp	133 hp	162 hp	195 hp
	KOHLER Command PRO OHV CH640	KOHLER Command PRO OHV CH740	KOHLER Command PRO OHV CH1000	General Motors Vortec DOHC	General Motors Vortec	General Motors Vortec	General Motors Vortec	General Motors Vortec	General Motors Vortec	General Motors Vortec
	V-Twin	V-Twin	V-Twin	Inline 4-Cylinder	V-6	V-8	V-8	V-8	V-8	V-8
	Hydraulic Valve Lifters									
Fuel	LPG (Liquid Propane)/NG (Natural Gas)							NG	LPG/NG	
Engine Cooling	Air				Liquid					
Enclosure	Galvanized Steel		100% Corrosion-Proof Composite		Galvanized Steel		Corrosion-Resistant Aluminum		Galvanized Steel (Aluminum Also Available)	
Sound Output dBA at 23 Ft	65		66*	68*	68	58	58	69	70	71
Dimensions (L x W x H) In	44 x 29 x 32		48 x 26 x 29		48 x 26 x 29		73 x 36 x 37		90 x 34 x 45	
Digital Voltage Regulation	+/- 1.5%				+/- 1.0%			+/- 0.5%		
Response Time	10 Seconds				10 Seconds			10 Seconds		
Warranty	5-Year Limited**						5-Year Limited***			

RATINGS: Standby ratings apply to installations served by a reliable utility source. All single-phase units are rated at 1.0 power factor. The standby rating is applicable to variable loads with an average load factor of 80% for the duration of the power outage. No overload capacity is specified at this rating. Ratings are in accordance with ISO-3046/1, BS5514, AS2789 and DIN 6271.

*At variable speed weekly exercise.

**Non-standby warranty of 18 months or 1000 hours available on 6VSG, 8.5/14RES models.

***5-year extended warranty is an included option for quick ship 40 – 125 kW models.

New Products



38RCL and 48RCL Generators

Provide more protection for homes and businesses with up to 200-amp electrical service in a small footprint. Ultra quiet, aluminum enclosure standard.



6VSG Generator

Efficiently charges battery banks for renewable energy, telecom and other remote applications. 24, 36 & 48 V direct current (DC) output available.

Accessories



Programmable Interface Module

Activates critical items like storm shutters or a security system when you're away from home. Requires OnCue System.



Load Control Module

Helps your generator balance high electrical loads by cycling them on and off.



RXT and RDT Transfer Switches

Automatically transfer power to and from utility and generator during an outage.



OnCue® Generator Management System

Provides true, remote monitoring and management of your system with online viewing and email notifications.